

53081	08	SAA5200	2	316L	G11B
①	②	③	④	⑤	⑥
0000	0000	0000000	0	0000	0000

**① BASE PART NUMBER**

5308 - Tri-Clamp Ball Valve (½-4" sizes)  
5309 - Butt-Weld Ball Valve (½-2" sizes)

NOTE: For pneumatic actuators add "1" to base part number.

**② SEAT MATERIAL**

0718 - Standard PTFE Seat  
0818 - Encapsulated PTFE Seat  
3218 - Reinforced (glass filled)  
3718 - Reinforced (glass filled)

Encapsulated PTFE Seat

\* For actuated valves, drop the "18" from the part number (e.g., use "07" for Standard PTFE Seat)

\*\* All reinforced (glass filled) seats have vent hole in ball.

**ACTUATOR**

Pneumatic Actuator/SS

**③ Stainless Steel**

SAA2000 - ½", ¾", 1", 1½" (12.7, 19.0, 25.4, 38.1mm), Air-to-Air

SAA5200 - 2" (50.8mm), Air-to-Air

SAA1030 - 3", 4" (76.2, 101.6mm), Air-to-Air

SSR2004 - ½" (12.7mm), Air-to-Spring

SSR5204 - ¾", 1", 1½" (19.0, 25.4, 38.1mm), Air-to-Spring

SSR1034 - 2" (50.8mm), Air-to-Spring

SSR2954 - 3", 4" (76.2, 101.6mm), Air-to-Spring

Aluminum

AA2000 - ½", ¾", 1", 1½" (12.7, 19.0, 25.4, 38.1mm)

Air-to-Air

AA5200 - 2" (50.8mm),

Air-to-Air

AA1030 - 3", 4" (76.2, 101.6mm),

Air-to-Air

SR3004 - ½" (12.7mm),

Air-to-Spring

SR3004 - ¾", 1" (19.0, 25.4mm),

Air-to-Spring

SR5204 - 1½" (38.1mm),

Air-to-Spring

SR7304 - 2" (50.8mm),

Air-to-Spring

SR2954 - 3", 4" (76.2, 101.6mm),

Air-to-Spring

**④ END CONNECTION SIZE**

½" (12.7mm) 2" (50.8mm)

¾" (19.0mm)

3" (76.2mm)

1" (25.4mm)

4" (101.6mm)

1½" (38.1mm)

**⑤ VALVE MATERIAL**

316L

**⑥ POSITION INDICATION AND SOLENOID OPTIONS**

Basic Switch Enclosure

G - NEMA 4 Enclosure (Standard)

X - NEMA 4, 4X, 7 & 9 Enclosure

**Cover**

1 - Flat Cover - No Position Indication

2 - Position Indicating Dome

**Switches**

0 - None

1 - (2) SPDT Mechanical Contact

2 - (2) SPST Proximity Sensor

**Standard Solenoid Valves**

0 - None

A - NEMA 4.4X 120 VAC

B - NEMA 4.4X 220 VAC

C - NEMA 4.4X 24 VAC

D - NEMA 4.4X, 7, 9, 120 VAC

E - NEMA 4.4X, 7, 9, 220 VAC

F - NEMA 4.4X, 7, 9, 24 VAC